model numbers and descriptions

RR-CIR2



IR Illumination Day/Night Color Camera with Audio Recording

RR-CVIR



Vandal Resistant IR Illumination Day/Night Color Camera

RR-CT



Vandal Resistant Color TearDrop Camera

RR-CD



Vandal Resistant Color **Dome Camera**

features

Location Type: Low-Light Recording: Audio Recording: Lens Type(s): Vandal Resistant: Horizonal Resolution:

Interior Standard: Disabled: RR-C2 Standard 2.5, 3.6, 6.0, 8.0 or 12.0mm Option w/ Enclosure: RR-CEIR Interior/Exterior Standard No 3.6mm Standard 380 TV lines

Interior/Exterior Nο

Varifocal, 4-8mm Standard 470 TV lines: RR-CT

540 TV lines: RR-CT-540

Interior/Exterior

Optional: RR-CD-540A Varifocal, 4-8mm Standard 470 TV lines: RR-CD 540 TV lines: RR-CD-540

specifications

Image Sensor S/N Ratio Video Output Audio Output Sync System

Sensitivity Shutter Speed White Balance LED Lighting Distance In/Output Connector

Power Supply **Power Consumption**

1/3 inch Sharp CCD More than 50dB

540 TV Lines

1.0 Vp-p (75 Ohms, Composite) 2 Vp-p

Internal

0.1 Lux Color / 0 Lux B/W $1/60 \sim 100,000$ Sec.

Auto Auto

5m (Low), 10m(High) Power (Red), Video Output (Yellow), Audio (White)

12VDC

Less than 160mA

1/3 inch SONY Super HAD CCD More than 48dB

1.0 Vp-p (75 Ohms, Composite)

2 Vp-p Internal

0.3 Lux

1/60 ~ 100,000 Sec.

Auto Auto

10m / 30 feet

Power (Red), Video Output (Yellow), Audio (White)

12VDC

Less than 250mA

1/3 inch Interline Transfer CCD 48dB (AGC Off)

1.0 Vp-p (75 Ohms, Composite)

N/A

Line lock (24V AC)/ Internal (12V DC)

1 lux

1/100,000 Sec.

Varifocal, 4-8mm 12V DC

N/A

Power (Red), Video Output

(Yellow) 12VDC

Less than 250mA

1/3 inch Interline Transfer CCD

48dB (AGC Off) 1.0 Vp-p (75 Ohms, Composite)

Line lock (24V AC)/

Internal (12V DC)

1 lux 1/100,000 Sec.

Varifocal, 4-8mm

12V DC


N/A


Power (Red), Video Output


(Yellow) 12VDC


Less than 250mA


dimensions

















Features and specifications are subject to change without notice



14148 NE 190th Street - Woodinville, WA 98072

Toll Free: 888-AVT-USA1; Tel: 425-483-7100; Fax: 425-483-7200

Video Surveillance Systems for Pupil Transportation

RR-MB1

Under-Seat Mounting Bracket Included with RR-INSB1

(School Bus Installation Kit)

- Easy to install under passenger or driver seats
- Durable stainless steel construction
- Reduces installation time
- Ensures proper mounting for the highest reliability



RR-MB2

Vertical Mounting Bracket Included with RR-INSB2 (School Bus Installation Kit)

- Provides an easy to install wall or panel mounting option for applications with limited space
- Durable stainless steel construction
- Reduces installation time
- Ensures proper mounting for the highest reliability



RR-ENV RR-ENVH

Environmental Protective Enclosure Environmental Protective Enclosure with Heater Sold Separately

- Durable stainless steel construction
- Locking front panel allows for secure and easy access to the DVR's removable hard disk drive
- Built-in heater option (Model No: RR-ENVH) for system recording from: -20°F to 130°F (-28.8°C to 54.4°C)
- Dimensions: 14.5" x 5.9" x 17.3" (WxHxD)

RR-ENVL RR-ENVLH

Environmental Protective Enclosure, Extra Length Environmental Protective Enclosure, Extra Length with Heater Sold Separately

- Durable stainless steel construction
- Locking front panel allows for secure and easy access to the DVR's removable hard disk drive
- Built-in heater option (Model No: RR-ENVLH) for system recording from:
- -20°F to 130°F (-28.8°C to 54.4°C)
- Dimensions: 14.5" x 5.9" x 19.8" (WxHxD)
- Extra length provides additional space for mounting accessories





Features and specifications are subject to change without notice

14148 NE 190th Street - Woodinville, WA 98072
Toll Free: 888-AVT-USA1; Tel: 425-483-7100; Fax: 425-483-7200

sales@avt-usa.com | www.avt-usa.com