















RoadRunner™ Camera Features and Specifications

>>>>> Video Surveillance Systems for Public Transit and Rail Applications

	RR-CIR2	RR-CVIR	RR-CT	RR-CD
				
	IR Illumination Day/Night Color Camera with Audio Recording	Vandal Resistant IR Illumination Day/Night Color Camera	Vandal Resistant Color TearDrop Camera	Vandal Resistant Color Dome Camera
features				
Location Type:	Interior	Interior/Exterior	Interior/Exterior	Interior/Exterior
Vandal Resistant:	Option w/ Enclosure: RR-CEIR	Standard	Standard	Standard
Low-Light Recording:	Standard; Disabled Optional	Standard	No	No
Audio Recording:	Standard	No	No	Optional
Lens Type(s):	2.5, 3.6, 6.0, 8.0 or 12.0mm	3.6mm	Varifocal, 4-8mm	Varifocal, 4-8mm
Horizontal Resolution:	540 TV lines	380 TV lines	Standard 470 TV Lines, High 540 TV lines	Standard 470 TV Lines, High 540 TV lines
specifications				
Image Sensor:	1/3 inch Sharp CCD	1/3 inch SONY Super HAD CCD	1/3 inch Interline Transfer CCD	1/3 inch Interline Transfer CCD
S/N Ratio:	More than 50dB	More than 48dB	48dB (AGC Off)	48dB (AGC Off)
Video Output:	1.0 Vp-p (75 Ohms, Composite)	1.0 Vp-p (75 Ohms, Composite)	1.0 Vp-p (75 Ohms, Composite)	1.0 Vp-p (75 Ohms, Composite)
Audio Output:	2 Vp-p	2 Vp-p	N/A	N/A
Sync System:	Internal	Internal	Line lock 24VAC/Internal 12VDC	Line lock 24VAC/Internal 12VDC
Sensitivity, LED Distance:	0 Lux, 10m (High) 5m (Low)	0.3 Lux; 10m / 30 feet	1 lux; N/A	1 lux; N/A
Shutter Speed:	1/60 ~ 100,000 Sec.	1/60 ~ 100,000 Sec.	1/100,000 Sec.	1/100,000 Sec.
White Balance:	Auto	Auto	Varifocal, 4-8mm	Varifocal, 4-8mm
AGC:	Auto	Auto	12V DC	12V DC
In/Output Connector:	Power (Red), Video Output (Yellow), Audio (White)	Power (Red), Video Output (Yellow), Audio (White)	Power (Red), Video Output (Yellow)	Power (Red), Video Output (Yellow)
Power Supply, Consumption:	12VDC, Less than 160mA	12VDC, Less than 250mA	12VDC, Less than 250mA	12VDC, Less than 250mA
diagrams & dimensions				
				
				

Features and specifications are subject to change without notice



14148 NE 190th Street - Woodinville, WA 98072
 Toll Free: 888-AVT-USA1; Tel: 425-483-7100; Fax: 425-483-7200
sales@avt-usa.com | www.avt-usa.com