

**High Speed Data Rate up to 54Mbps**Capable of handling heavy data payloads such as MPEG video streaming

**IEEE 802.11b/g Compliant** 

Fully Interoperable with IEEE 802.11b/IEEE 802.11g compliant devices

Point-to-point/multipoint Wireless Connectivity
Transfer data between multiple vehicles

True Plug and Play Device No drivers are necessary

Full WPA & IEEE802.1x supplicant support Powerful data security

Hide SSID (AP Mode)

Prevents unauthorized users from sharing the bandwidth, increases efficiency of the network

**DHCP Client/ Server** 

Simplifies network administration

WDS (Wireless Distribution System)

Configures wireless access point and bridge mode simultaneously as a wireless repeater

MAC Address Filtering (AP Mode)

Ensures secure network connections

**Controllable Output Power** 

For maximum flexibility in deployment options

SNMP v1/ v2 Support

Provides easy remote management

Features and specifications are subject to change without notice



14148 NE 190th Street - Woodinville, WA 98072
Toll Free: 888-AVT-USA1; Tel: 425-483-7100; Fax: 425-483-7200
sales@avt-usa.com | www.avt-usa.com

The RoadRunner™ Wireless LAN operates seamlessly in the 2.4 GHz frequency spectrum, the transmitter and receiver support the 802.11b (2.4GHz, 11Mbps) and the new, faster 802.11g (2.4GHz, 54Mbps) wireless standards.

Designed for use with the RoadRunner™ Mobile Digital Video System, the client bridge features security enhancement functionalities like EAP-TTLS and

supports a multitude of certified solutions such as 802.3af Power over Ethernet. The WR-200 is the perfect solution for mobile video applications.

RR-WR200: Wireless LAN High Powered Receiver

RR-WT200: Wireless LAN High Powered Transmitter and Vehicle Antenna

Specifications

**RADIO** 

Frequency Band 2.4 - 2.484Ghz
Media Access Protocol Carrier Sense Multiple Access with Collision Avoidance

Radio Type Direct Sequence Spread Spectrum (DSSS)

Operation Channels 11 for North America

Typical RF Output Power 25 +/- 2dBm@1, 2.5, 5 & 11Mbps, 23 +/- 2dBm@6, 9, 12 & 18Mbps 22 +/- 2dBm@24 & 36Mbps, 21 +/- 2dBm@48 & 54Mbps

22 +/- 2ubiii@24 α σοίνισμος, 21 +/- 2ubiii@

Antenna Connector TNC Type, Female Reverse Typical Receive Sensitivity -94dBm @ 1Mbps, -92dBm

-94dBm @ 1Mbps, -92dBm @ 2Mbps, -89dBm @ 5.5Mbps, -86dBm @ 11Mbps, -92dBm @ 6Mbps, -90dBm @ 9Mbps, -88dBm @ 12Mbps, -96dBm @ 18Mbps, -83dBm @ 24Mbps, -79dBm @ 36Mbps, -74dBm @ 48Mbps, -72dBm @ 54Mbps

Modulation OFDM DBPSK @ 1Mbps DQPSK @ 2Mbps

CCK @ 5.5 & 11Mbps BPSK @ 6 & 9Mbps QPSK @ 12 & 18Mbps 16-QAM @ 24 & 36Mbps 64-Qam @ 48 & 54Mbps

NETWORK

Network Topology Ad-Hoc, Infrastructure

Operation Modes Point-to-point/Point-to-Multipoint Bridge/Access point/

Client Bridge/WDS

Interface 1x 10/100Mps RJ-45 LAN Port Supported OS Windows 98SE, ME, 2000, XP Roaming IEEE802.11b compliant

Security IEEE802.1x Authenticator/ RADIUS Client EAP-MD5/TLS/TTLS

support in Access Point Mode, WPA/Pre-share Key (PSK)/TKIP MAC Address Filtering, Hide SSID in beacons, Layer 2 isolation

IP Auto Configurations DHCP Client/Server

SPECIFICATIONS

Data Rates 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, 54Mbps

Standards: IEEE802.11b, IEEE802.1x, IEEE802.3, IEEE802.3u, IEEE802.11g, IEEE802.11b/g

Operating: -10°C to +60°C; Storage: -40°C to +70°C

Power Requirements Power Supply 110VDC, Device 12V/1A Status LEDs LAN-Link, WLAN-Link, Power- on/off

Regulation Certifications LAN-LINK, WLAN-LINK, Power- on/of FCC Part 15/UL, ETSI300/ 328/ CE

**ENVIRONMENT** 

Temperature Range

Humidity 5% ~ 95% (non-condensing)

**MANAGEMENT** 

Configuration Web-based configuration HTTP Telnet configuration

SNMP V1/V2C MIBI, MIBII

Fireware Upgrade Upgrade Firmware via web-browser