

OpenEye®



360°



rotate

83°



tilt

OpenEye's 170-Series dome is a cost-effective, compact, vandal proof indoor/outdoor camera solution. Protected by a high-grade polycarbonate housing, the 170-Series dome comes equipped with an integrated quick-mount feature allowing for easy installation without screws or anchors.

HIGHLIGHTS

- » 4mm-9mm Vari-Focal Lens
- » Ultrasonically Welded Polycarbonate Dome
- » Integrated Quickmount Capable
- » Backlight Compensation
- » Turbo Auto Gain Control
- » Auto White Balance
- » 3/4" & 1/2" Conduit Mounting Points

170 SERIES

INDOOR/OUTDOOR DOME

170-SERIES INDOOR/OUTDOOR DOME

VANDAL PROOF

The 170-Series is compatible with OpenEye's Quickmount bracket for easy installation and supports mounting directly to single-gang electrical boxes as well as providing connection points for 3/4" and 1/2" conduit. With its triple-wall polycarbonate construction, the 170-Series dome is able to withstand almost any major impact.

LENS SPECIFICATIONS

Focal Length	4mm~9mm
F-No.	F1.6
Iris Range	F1.6~F2.4
Minimum Object Distance	50cm(19.7")
Field Of View	Diagonal: 92.8°~39.4° Horizontal : 71.0°~31.6° Vertical: 51.6°~23.6°
BLC	ON/OFF
AGC-UP	ON/OFF
Low Light Chroma Suppression	AUTO

CAMERA ACCESSORIES Optional Accessories Sold Separately


CA-3004SM - 4S Electrical Box Mount

CA-300PMK - Pendant Cap Mount

CA-300WB - Wall Bracket Mount

CA-300C - Corner Mount

CA-300P - Pipe Adaptor



Measurements are in millimeters

FEATURES

- » Day/Night Operation
- » SONY 1/3 Super HAD CCD Color Sensor
- » Supports NTSC
- » 2 Composite Outputs: 1 BNC / 1 1/8" mini jack
- » 50dB Signal to Noise Ratio
- » Back Light Compensation on Center Area
- » Vandal Proof Polycarbonate Dome
- » Easy to Install
- » Small Form Factor
- » Both Indoor and Outdoor Use
- » Included Flush Mount Kit
- » Weather Resistant

PRODUCT SPECIFICATIONS

Type / Format	NTSC
Scanning Element	2:1 Interlace H15.734KHz / V :59.9Hz
Effective Picture Element	768(H) x 494(V)
Image Picture Element	1/3" CCD Sony Super HAD
Resolution (TV lines)	480
Minimum Illumination	1.2 Lux @ F1.6
S/N Ratio	48dB
Back Light Compensation	Central Area for DC IRIS Lens
Exposure Control	DC Type Auto IRIS Control
Sync System	INT
Gamma Compensation	0.45
Video Output	1.0Vpp, 75Ω Unbalanced
White Balance	Automatic White Balance
Auto White Balance Range	2500°K - 9700°K
Power Range	DC 12V ±10%
Power Consumption	2.2W (Max)
Operating Temperature	14°F (-10°C) ~ 122°F (50°C)
Storage Temperature	-4°F (-20°C) ~ 140°F (60°C)
Housing / Dome Cover	White / Clear

CAMERA MODELS

CM-170 - Indoor/Outdoor Vandal Proof Dome Camera

OpenEye

North America

888.542.1103 Toll Free • 509.232.5261

509.777.6702 Fax • Liberty Lake, WA • www.openeye.net



28568AB

Copyright ©2008 OpenEye, Inc. All Rights Reserved. Information contained in this document is subject to change without prior notice. OpenEye does its best to provide accurate information but cannot be held responsible for typos or mistakes.

A12931